



MATERIAL SAFETY DATA SHEET

PRODUCT TRADE NAME:

HOMAX PRODUCTS, INC.
POPCORN WALL PATCH
ITEM #8520, 8522, 5210, 5220, 5225

HAZARDOUS MATERIAL INFORMATION SYSTEM	
HEALTH	0
FLAMMABILITY	0
REACTIVITY	0
PROTECTIVE EQUIPMENT	A

(HAZARD RATING: 0=LEAST, 1=SLIGHT, 2=MODERATE, 3=HIGH, 4=EXTREME) (A= Safety Glasses)

SECTION I - MANUFACTURER IDENTIFICATION

MANUFACTURER'S NAME:
 HOMAX PRODUCTS, INC.
 468 WEST HORTON ROAD
 BELLINGHAM, WA 98226

24 HOUR EMERGENCY PHONE NUMBER:
 CHEMTREC 1-800-424-9300

INFORMATION PHONE NUMBER: 1-800-729-9029

DATE OF PREPARATION: 01/15/03

SECTION II - HAZARDOUS INGREDIENTS/IDENTITY INFORMATION

CAS NUMBER	DESCRIPTION	Hazardous Components			
		% by wt.	SARA	Vapor pressure (mm Hg @ 20 C)	LEL (@ 25 C)
1317-65-3	Calcium Carbonate	30-35	NO	N/A	N/A
12001-26-2	Siliceous Muscovite Mica	1-5	NO	N/A	N/A
93763-70-3	Expanded Perlite	1-5	NO	N/A	N/A

*** Warning: This product contains a chemical known to the state of California to cause cancer.

N/A = not applicable

CAS NUMBER	(OEH) PSL/TWA	Occupational Exposure Limits		
		PEL/CEILING	PEL/STEL	Skin
1317-65-3	N/E	N/E	N/E	N/E
12001-26-2	20 mppcf	N/E	N/E	N/E
93763-70-3	N/E	N/E	N/E	N/E
CAS NUMBER	(ACGIH) TLV/TWA	Occupational Exposure Limits		
		TLV/CEILING	TLV/STEL	Skin
1317-65-3	10 mg/m3 Total Dust	N/E	N/E	N/E
12001-26-2	3 mg/m3 Respirable Due	N/E	T	N/E
93763-70-3	N/E	N/E	N/E	N/E

*** The dried film of this product may become a dust nuisance when removed by sanding or grinding. OSHA recommends a PEL/TWA of 15 mg/m³ for total dust and 5 mg/m³ for the respirable fraction. ACGIH recommends a TLV/TWA of 10 mg/m³ for total dust.

*** Skin absorption may contribute to the overall exposure to the overall exposure to this material – Take appropriate measures to prevent skin contact.

(NE – not established)

SECTION III - PHYSICAL/CHEMICAL CHARACTERISTICS

BOILING POINT:	not established
VAPOR DENSITY:	> 1 (air = 1)
% VOLATILE BY VOLUME:	0
EVAPORATION RATE:	< 1 (ether = 1)
% VOLATILE BY WEIGHT:	0
KILOGRAMS PER LITER:	.969 (Theoretical)

SECTION IV – HEALTH INFORMATION

EYE CONTACT:	ANY FOREIGN MATERIAL GOTTEN INTO THE EYE MAY CAUSE IRRITATION
SKIN CONTACT:	EXPOSURE MAY PRODUCE SKIN IRRITATION
INHALATION:	EXPOSURE MAY PRODUCE IRRITATION TO THE NOSE, THROAT, RESPIRATORY TRACT, AND OTHER MUCOUS MEMBRANES.
INGESTION:	THIS PRODUCT MAY BE IRRITATING TO THE GASTROINTESTINAL TRACT IF INGESTED.

SIGNS & SYMPTOMS

SYMPTOMS OF EYE IRRITATION INCLUDE PAIN, TEARING, REDDENING AND SWELLING. SYMPTOMS OF SKIN IRRITATION INCLUDE REDDENING, SWELLING, RASH AND REDNESS, SYMPTOMS OF RESPIRATORY IRRITATION INCLUDE RUNNY NOSE, SORE THROAT, COUGHING, CHEST DISCOMFORT, SHORTNESS OF BREATH AND REDUCED LUNG FUNCTION. SYMPTOMS OF GASTROINTESTINAL IRRITATION INCLUDE SORE THROAT, ABDOMINAL PAIN, NAUSEA, VOMITING AND DIARRHEA.

AGGRAVATED MEDICAL CONDITIONS

PREEXISTING SKIN, EYE AND RESPIRATORY DISORDERS MAY BE AGGRAVATED BY EXPOSURE TO THIS PRODUCT.

OTHER HEALTH EFFECTS NONE RECOGNIZED

SECTION V – EMERGENCY AND FIRST AID PROCEDURES

EYE CONTACT

IMMEDIATELY FLUSH EYES WITH WATER FOR AT LEAST 15 MINUTES. SEEK MEDICAL ATTENTION IF ANY SYMPTOMS PERSIST.

SKIN CONTACT

REMOVE CONTAMINATED CLOTHING AND SHOES. WIPE EXCESS FROM SKIN AND FLUSH WITH WATER USING SOAP IF AVAILABLE. SEEK MEDICAL ATTENTION IF IRRITATION OCCURS. DO NOT REUSE CLOTHING UNTIL THOROUGHLY DECONTAMINATED.

INHALATION

REMOVE VICTIM TO FRESH AIR AND TREAT SYMPTOMATICALLY. PROVIDE OXYGEN IF BREATHING IS DIFFICULT. GIVE ARTIFICIAL RESPIRATION IF THE VICTIM IS NOT BREATHING. SEEK PROMPT MEDICAL ATTENTION.

INGESTION

DILUTE WITH LIQUID UNLESS THE VICTIM IS UNCONSCIOUS OR VERY DROWSY. IF VOMITING SPONTANEOUSLY OCCURS, KEEP THE VICTIM'S HEAD BELOW THE HIPS TO PREVENT ASPIRATION INTO THE LUNGS – CONSULT A PHYSICIAN, HOSPITAL OR POISON CONTROL CENTER AND/OR TRANSPORT TO EMERGENCY FACILITY IMMEDIATELY.

SECTION VI – FIRE AND EXPLOSION HAZARDS

FLAMMABILITY CLASSIFICATION:	N/A
FLASH POINT:	N/A
EXTINGUISHING MEDIA:	N/A
SPECIAL FIRE RIGHTING PROCEDURES AND PRECAUTIONS:	N/A
UNUSUAL FIRE AND EXPOSION HAZARDS:	N/A

SECTION VII - REACTIVITY

STABILITY:	STABLE
HAZARDOUS POLYMERIZATION:	WILL NOT OCCUR
CONDITIONS AND MATERIALS TO AVOID:	NONE RECOGNIZED
HAZARDOUS DECOMPOSITION PRODUCTS:	CARBON DIOXIDE, CARBON MONOXIDE AND UNIDENTIFIED ORGANIC COMPOUNDS MAY BE FORMED DURING COMBUSTION.

SECTION VIII – EMPLOYEE PROTECTION

RESPIRATORY PROTECTION

USE VENTILATION AS REQUIRED TO CONTROL VAPOR CONCENTRATION – AT LEAST 10 AIR CHANGES PER HOUR ARE RECOMMENDED FOR GOOD GENERAL ROOM VENTILATION. IF EXPOSURE EXCEEDS THE PEL/TLV, USE THE APPROPRIATE NIOSH-APPROVED RESPIRATOR.

PROTECTIVE CLOTHING

WEAR SAFETY GLASSES, GOGGLES, OR A SPLASH SHIELD TO PREVENT EYE CONTACT. CONTACT LENSES SHOULD NOT BE WORN. WEAR NEOPRENE OR OTHER CHEMICAL RESISTANT GLOVES TO PREVENT SKIN CONTACT.

ADDITIONAL PROTECTIVE MEASURES

EYE WASH FOUNTAINS AND SAFETY SHOWERS SHOULD BE AVAILABLE FOR USE IN AN EMERGENCY.

SECTION IX – ENVIRONMENTAL PROTECTION

SPILL OR LEAK PROCEDURES

LARGE SPILLS – EVACUATE THE HAZARD AREA OF UNPROTECTED PERSONNEL. WEAR APPROPRIATE RESPIRATOR AND PROTECTIVE CLOTHING. SHUT OFF SOURCE OF LEAK ONLY IF SAFE TO DO SO. DIKE AND CONTAIN. IF VAPOR CLOUD FORMS, WATER FOG MAY BE USED TO SUPPRESS; CONTAIN RUN-OFF. REMOVE WITH VACUUM TRUCKS OR PUMP TO STORAGE/SALVAGE VESSELS. SOAK UP RESIDUE WITH AN ABSORBENT SUCH AS CLAY, SAND OR OTHER SUITABLE MATERIAL; PLACE IN NON-LEAKING CONTAINERS FOR PROPER DISPOSAL. FLUSH AREA WITH WATER TO REMOVE TRACE RESIDUE; DISPOSE OF FLUSH SOLUTIONS AS ABOVE.

SMALL SPILLS-TAKE UP WITH AN ABSORBENT MATERIAL AND PLACE IN NON-LEAKING CONTAINERS; SEAL TIGHTLY FOR PROPER DISPOSAL.

SECTION X – ADDITIONAL PRECAUTIONS

KEEP LIQUID AND VAPOR AWAY FROM HEAT, SPARKS, AND FLAME. EXTINGUISH PILOT LIGHTS, CIGARETTES AND TURN OFF OTHER POSSIBLE SOURCES OF IGNITION PRIOR TO USE AND UNTIL VAPORS ARE GONE. SURFACES THAT ARE SUFFICIENTLY HOT MAY IGNITE PRODUCT IN THE ABSENCE OF SPARKS OR FLAME. VAPORS MAY ACCUMULATE AND TRAVEL TO IGNITION SOURCES DISTANT FROM HANDLING SITE. KEEP CONTAINERS CLOSED WHEN NOT IN USE. USE WITH ADEQUATE VENTILATION. CONTAINERS, EVEN IF EMPTY, CAN CONTAIN EXPLOISIVE VAPORS. DO NOT CUT, DRILL, GRIND, OR WELD NEAR CONTAINERS.

CONTAINERS CAN CONTAIN HAZARDOUS PRODUCT RESIDUES EVEN WHEN EMPTY. WASH WITH SOAP AND WATER BEFORE EATING, DRINKING, SMOKING, OR USING TOILET FACILITIES.

SECTION IX - DISCLAIMER

TO THE BEST OF OUR KNOWLEDGE, THE INFORMATION CONTAINED HEREIN IS ACCURATE, OBTAINED FROM SOURCES BELIEVED BY HOMAX PRODUCTS, INC. TO BE ACCURATE. SINCE THE CONDITIONS AND METHODS OF USE OF OUR PRODUCTS ARE BEYOND OUR CONTROL, WE DISCLAIM ANY AND ALL LIABILITY ARISING OUT OF THE IMPROPER USE OF THESE PRODUCTS OR THE INFORMATION PROVIDED HEREWITH.